



(12) **United States Patent**  
**Hahne et al.**

(10) **Patent No.:** **US 6,933,851 B2**  
(45) **Date of Patent:** **Aug. 23, 2005**

(54) **AIR TRAVEL SECURITY METHOD, SYSTEM AND DEVICE**

(76) Inventors: **Per K. Hahne**, 303 Trafalgar Rd., Oakville, ON (CA), L6J 3H1; **Ray Wark**, 8218 Tenth Line N., Halton Hills, ONT (CA), L0P 1K0

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 268 days.

(21) Appl. No.: **10/225,071**

(22) Filed: **Aug. 21, 2002**

(65) **Prior Publication Data**

US 2003/0214418 A1 Nov. 20, 2003

**Related U.S. Application Data**

(60) Provisional application No. 60/381,368, filed on May 20, 2002.

(51) **Int. Cl.**<sup>7</sup> ..... **G08B 23/00**

(52) **U.S. Cl.** ..... **340/573.4; 340/573.1; 340/539.11; 340/505**

(58) **Field of Search** ..... 340/505, 506, 340/539.1, 539.11, 573.1, 573.4, 945; 244/118.5; 361/179, 232; 235/375, 462

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,835,673 A 9/1974 Kwan

4,943,885 A \* 7/1990 Willoughby et al. .... 361/232  
5,159,344 A \* 10/1992 Robinson et al. .... 342/44  
5,401,944 A \* 3/1995 Bravman et al. .... 235/375  
5,528,450 A 6/1996 Willoughby et al.  
5,841,622 A \* 11/1998 McNulty, Jr. .... 361/232  
6,147,602 A \* 11/2000 Bender ..... 340/568.1  
6,246,320 B1 \* 6/2001 Monroe ..... 340/506  
6,766,039 B1 \* 7/2004 Al-Sheikh ..... 382/115

**FOREIGN PATENT DOCUMENTS**

DE 10150929 \* 10/2001

\* cited by examiner

*Primary Examiner*—Van T. Trieu

(57) **ABSTRACT**

A method of providing air travel security for passengers traveling via an aircraft comprises situating a remotely activatable electric shock device on each of the passengers in position to deliver a disabling electrical shock when activated; and arming the electric shock devices for subsequent selective activation by a selectively operable remote control disposed within the aircraft. The remotely activatable electric shock devices each have activation circuitry responsive to the activating signal transmitted from the selectively operable remote control means. The activated electric shock device is operable to deliver the disabling electrical shock to that passenger.

**59 Claims, 14 Drawing Sheets**

